

Technische gegevens

O: optioneel x: niet mogelijk

type (maat)	Nom. vermogen kW	Bereik kW	Rendement %	rookgasafvoer Ø mm	gewicht kg	hout in cm	rookgasafvoerreductie Ø 150mm	EN13229
insert ECO								
60/50	6,6	3-8,8		180	142	45	O	V
70/50	6,7	4,5-9	75	180	163	50	O	V
80/50	7,1	5,5-9,5	75	180	178	50	X	V
90/50	7,5	6,0-10,0	75	180	198	50	X	V
100/50	8,2	8-11	75	180	218	50	X	V
60/60	6,9	4,7-9,2	75	180	156	45	O	V
70/60	8,0	6,2-10,7	75	180	178	50	O	V
80/60	8,4	7-11,2	75	180	200	50	X	V
90/60	8,7	7,9-11,7	75	180	200	50	X	V
100/60	10,0	8,5-13,4	75	180	236	50	X	V
DF80/60	8,4	7,0-11,2	75	180	236	50	X	V
DF100/60	10,0	8,5-13,4	75	180	292	50	x	V
V 70/60	8,0	6,2-10,7	75	180	188	50	O	V
V 80/60	8,0	6,2-10,7	75	180	210	50	X	V
V100/60	10,0	8,5-13,4	75	180	227	50	X	V
Box'r ECO / Wall'r ECO								
60/50 b/w	6,6	3-8,8	75	180	183	45	O	V
70/50 b/w	6,7	4,5-9	75	180	212	50	O	V
80/50 b/w	7,1	5,5-9,5	75	180	229	50	X	V
90/50 b/w	7,5	6-10	75	180	255	50	X	V
100/50 b/w	8,2	8-11	75	180	282	50	X	V
60/60 b/w	6,9	4,7-9,2	75	180	197	45	O	V
70/60 b/w	8,0	6,2-10,7	75	180	232	50	O	V
80/60 b/w	8,4	7,0-11,2	75	180	246	50	X	V
90/60 b/w	8,7	7,9-11,7	75	180	275	50	X	V
100/60 b/w	10,0	8,5-13,4	75	180	301	50	X	V
DF80/60	8,4	7,0-11,2	75	180	301	50	X	V
DF100/60	10,0	8,5-13,4	75	180	352	50	X	V